

H2ONDA

ABOVE SINK WATERCOOLER || ELECTRIC SUPPLY

Modern watercooler studied for office use.

Its unique thermoplastic polyester front can be personalized according to the customer's tastes.

As standard, the dispenser is equipped with anti-flooding and LED bactericidal system.

AVAILABLE COMBINATIONS COLOURS

BACK/ FRONT:

- ★ WHITE/WHITE
- ★ BLACK/BLACK
- ★ STEEL/WHITE
- ★ STEEL/BLACK



Dispenser	Production of cooled water	Cooling	Weight	Sizes (LXPXH) *
H2Onda Plus 3 supplies	15 l/h	storage tank	21 Kg	28x43x41
H2Onda Natural 2 supplies	15 l/h	storage tank	14 Kg	28x36x41

**drip tray included*

The production of still and sparkling cold water, below 10°C, is closely linked to the room temperature but mainly to the inlet water temperature.

H2ONDA

ABOVE SINK WATERCOOLER || ELECTRIC SUPPLY

TECHNICAL CHARACTERISTICS:

Material of the bodywork: Painted sheet metal

Water pressure: 2-3,5° bar

Max inlet temperature: 10-35°

Water feeding (min-max): 10-25°C

Feeding: 220v - 50 Hz

On/off button (only in natural version)

DISPENSER || H2Onda

Compressor: 1/20" Hp

Storage tank capacity:

- 1,6 l Plus version
- 2,5 l Natural version

Carbonator capacity: 100 l/h

Carbonator pump: PDP 100 l/h

Recirculating pump: NOT PROVIDED

Power consumption: 220 W

Voltage: 230 V- 50 Hz



CERTIFIED PRODUCT
MATERIALS IN CONTACT WITH WATER



USABLE WITH A FILTER WATER CARE FILTERS.



USABLE ONLY WITH DRINKING WATER.



EQUIPMENT COMPLIES WITH:
 D.M. 25/2012 - D.M. 174/2004

NOTE: This equipment requires regular maintenance periodically to ensure the requirements of potability of the drinking water treated and maintenance improvements as declared by the producer. Do not use with microbiologically dangerous water. After long periods of inactivity (3-4 weeks) to keep it carefully sanitizing or provide for the replacement of the filter.