



LAGUNA

UPPERCOUNTER DISPENSER || ELECTRIC SUPPLY

LAGUNA is the uppercounter with an Italian design that combines the need of high performance to compactness.

Compact and functional, it connects to the water supply to supply cold, still, sparkling or hot water.

Perfect for use in the workplace.

The equipment is standard equipped with an anti-flooding system and the UV LED bactericidal system.

AVAILABLE COLOUR

BODYWORK / FRONT

- ★ white/white
- ★ black/black
- ★ inox/withe
- ★ inox/black



Dispenser	Productivity	Cooling	Weight	Sizes (LXPXH) * uppercounter version
Laguna Plus 3 supplies	15 l/h	accumulation	21 Kg	28x43x41
Laguna Natural 2 supplies	15 l/h	accumulation	14 Kg	28x43x41
Laguna Hot 4 supplies	15 l/h	accumulation	21 Kg	28x43x41
Laguna Vending Plus 3 supplies	15 l/h	accumulation	21 Kg	28x43x41
Laguna Vending Natural 2 supplies	15 l/h	accumulation	14 Kg	28x43x41

including drip tray

The production of still and / or sparkling cold water, below 10 °C, is closely linked to the temperature environment but mainly at the temperature of the incoming water.



LAGUNA

UPPERCOUNTER DISPENSER || ELECTRIC SUPPLY

Features of the product :

Bodywork material: painted sheet metal

Water supply pressure: 2- 3.5 bar

Operating ambient temperature: 10 - 35 ° C

Feed water temperature (min-max): 10-25 ° C

Power supply: 220 V- 50 Hz single-phase

On / off switch (present only in the natural version)

TECHNICAL FEATURES:

Compressor: 1/20 "Hp

Accumulation tank capacity:

- 1.6 l for the Plus version
- 2.5 for the Natural version

Carbonator power: 100 l / h

Carbonator Pump: Volumetric 100 l / h

Recirculation pump: NOT PRESENT

Carbonator liters: 0,8 l (not present in the Natural version)

Power consumption: 220 W

Voltage: 230 V- 50 Hz



**CERTIFIED PRODUCT
MATERIALS IN CONTACT WITH WATER**



USABLE UNDER COUNTER DISPENSER



USABLE ONLY WITH DRINKING WATER



**APPLIANCE COMPLIANT WITH A:
D.M. 25/2012 – D.M. 174/2004**

Vertical operation. MAX inlet temperature: 35 ° C.
MAX operating pressure: 3.5bar.

ATTENTION: this equipment requires regular periodic maintenance in order to ensure the potability requirements of the treated drinking water and the maintenance of improvements as declared by the manufacturer. Do not use with microbiologically dangerous water. After periods of inactivity (3-4 weeks) carry out a thorough sanitization or replace the filter.