



EUROS 200

UNDERCOUNTER WATER COOLER||

Top range for the production of chilled still, sparkling chilled and ambient micro-filtered water.

Frigogasatore intended purely for professional use, guarantees maximum production capacity, satisfying even the most demanding requests.

It has a powerful and balanced ICE COUNTER refrigerant circuit designed for immediate recovery and quick start-up, using only ecological gases.

It offers maximum hygiene and simple maintenance.



3 DISPENSES: ambient temperature, refrigerated still and sparkling refrigerated.

Dispenser	Productivity	Cooling	Weight	Dimensions (LXPXH)
Euros 200 3 distributions	200 l/h	Ice bank	65 Kg	42x74x62 cm



EUROS 200

DUNDERCOUNTER WATER COOLER ||

PRODUCT FEATURES:

Body material: Painted sheet metal

Water supply pressure: 1 - 3,5 bar

Operating ambient temperature: 10 - 35° C

Water supply temperature (min-max): 10-25° C

Power supply: 220/240 V- 50 Hz monofase

On/off Switch

TECHNICAL FEATURES:

Compressor: 1/2" Hp

Gasator volume: 1,7 l

Ice bank capacity: 35 kg

Gasator liters: 2 l

Carbonator power: 400 l/h

Refrigerant Gas: R 134 a

Recirculation pump: NON PRESENT

Consumption power: 840 W

Voltage: 230 V- 50 Hz



CERTIFIED PRODUCT
MATERIALS IN CONTACT WITH WATER



USABLE WITH A FILTER WATER CARE FILTERS.



USABLE ONLY WITH POTABLE WATER



EQUIPMENT COMPLIES WITH:
D.M. 25/2012 - D.M. 174/2004

Vertical operation. MAX inlet temperature: 35 ° C.
MAX operating pressure: 3.5bar.

ATTENTION: this equipment requires regular periodic maintenance in order to ensure the potability requirements of the treated drinking water and the maintenance of improvements as declared by the manufacturer. Do not use with microbiologically dangerous water. After periods of inactivity (3-4 weeks) carry out a thorough sanitization or replace the filter.